



# Vectra®

## Floor Finish

Vectra® Floor Finish saves time while giving floors diamond-like brilliance, clarity and durability.

### Features & Benefits

- Provides diamond-like clarity and gloss
- Cures on the floor faster than traditional floor coatings, resulting in time and labor savings
- Resists dirt embedment, black heel marks, scratching and scuffing
- Versatile finish responds well to 175 - 1500 RPM and UHS equipment
- Reduced VOCs of 54.4% results in significantly decreased odors
- Solids content 19%
- Meets ASTM D-2047 slip resistance requirements

### Applications

- For use on resilient and most hard surface flooring
- A sealer may be required for highly polished stone surfaces, glazed ceramic tile, luxury vinyl tile, and some rubber floors
- Not intended for use on cork, wood, or bamboo flooring



**Use Instructions**

- Blockade areas to be stripped or finished. Position wet-floor signs around area to be cleaned.
- Strip floor using recommended Diversey brand stripper according to label directions

**Coating**

- Apply 2-3 uniform coats using a clean finish mop or the Diversey ProSpeed™/MC or TrailBlazer™/MC Floor Finish Applicator System. Apply additional coats until desired gloss is obtained.
- Allow 30 minutes drying time between coats. Temperature, humidity and ventilation may affect drying time. Allow finish to cure for 24 hours before buffing.

**Maintenance**

- Dust mop or sweep
- Clean the floor with a mop or an automatic scrubber using the recommended Diversey brand cleaner following label directions
- If desired, spray buff using recommended Diversey brand floor maintainer to enhance gloss

**Recoating**

- Dust mop or sweep
- Deep scrub floor using Diversey cleaner according to label directions
- Blockade area and apply 1-2 uniform coats of finish using a clean finish mop or the Diversey ProSpeed™/MC or TrailBlazer™/MC Floor Finish Applicator System. Allow finish to cure for 24 hours before buffing.

**Removal**

- Remove using recommended Diversey brand stripper according to label directions

**Best Results**

- Do not dilute
- Do not use on surfaces colder than 50°F (10°C) @ 15% RH
- To avoid contamination, do not return unused product to original container

**Note:** Floors will be slippery when wet or contaminated with foreign materials. Promptly clean-up spills and foreign materials. Meets ASTM D2047 requirements for slip resistance.

Technical data	Vectra® Floor Finish
Color/Form	Opaque Off-White Liquid
pH	8.6
Scent	Ammonia
Shelf Life	2 Years

Product	Pack size	Dilution	Product code	
Vectra® Floor Finish	6 x 2.5 L / 2.64 Qt. ProSpeed™/MC BIB (Bag-in-Box)	Ready-to-use	4971921	
Vectra® Floor Finish	4 x 1 gal. / 3.78 L Containers	Ready-to-use	04078	
Vectra® Floor Finish	1 x 5 gal. / 18.9 L Envirobox™/MC	Ready-to-use	5105047	
Vectra® Floor Finish	1 x 2.5 gal./9.46 L Envirobox™/MC	Ready-to-use	101102886	

**Safe handling**

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use; and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDS are available online at [www.diversey.com](http://www.diversey.com) or by calling 888.352.2249. Improper use or dilution may result in damage to surfaces and may result in health and physical hazards that match those of the concentrate. Please refer to the Diversey HazMat Library, only available through Internet Explorer, <http://naextranet.diversey.com/dot/>, for up-to-date shipping information.