

WV 1800 / I802P

WV 1800 Wet Vacuums (DH models) and Continuous Pumper Vacuums (P models)

- The DH models have a large diameter dump hose for fast draining, while the P models incorporate a sump pump enabling continuous pumping of fluid without interrupting the vacuuming process
- The WV 1800 series features one 1200 watt vacuum motor while the WVD series feature two 800 watt motors for when more power is needed
- Manufactured from structural foam backed by 10-year warranties
- The wet shutoff assembly features a ball that rotates continually, staying clean and free from debris while protecting the motor
- Prolong motor life by adding a 13" floor pad to the top of the wet float creating a barrier that prevents foam or stripper from reaching the motor



Continuous pumper unit



I800 SERIES



QUIET Technology



TIME Saver

WV 1800P / WVD 1802P Continuous Pumper Key Features

- Continuously recovers and pumps liquid at a rate of 60 gallons per minute on a flat surface
- Able to pump liquid at a rate of 7 gallons per minute up 22 feet in the air
- Ideal for floods, water pipe ruptures, drain back-ups, and industrial spills
- Submersible pump is made of durable, stainless steel for heat and chemical resistance
- Stainless steel shaft and triple seal system with thermal protection to prevent overheating

MODEL	WV 1800DH	WVD 1802DH	WV 1800P	WVD 1802P
Motor	1,200 W, 1.6 Hp	2-800 W, 1 Hp	1,200 W, 1.6 Hp	2-800 W, 1 Hp
Motor Life	1,100 hours	1,100 hours	1,100 hours	1,100 hours
Water Lift	100"	90"	100"	90"
Airflow	95 cfm	160 cfm	95 cfm	160 cfm
Capacity - Wet	20 gal.	20 gal.	20 gal.	20 gal.
Power Cord	42'	42'	42'	42'
Weight	81 lb	86 lb	85 lb	90 lb
Tank Construction	Structural Foam	Structural Foam	Structural Foam	Structural Foam
Head	Structural Foam	Structural Foam	Structural Foam	Structural Foam
Pump Power			500W	500W
Output			60 gpm	60 gpm
Type			Centrifugal	Centrifugal